



AZ 16-02ZVRK-M20

- 3 cable entries M 20 x 1.5
- Large wiring compartment
- Thermoplastic enclosure
- Double-insulated
- 52 mm x 90 mm x 30 mm
- Universal coding
- Long life
- High level of contact reliability with low voltages and currents
- Insensitive to soiling
- Slotted holes for adjustment, circular holes for location

Data

Ordering code	
Product type description	AZ 16-02ZVRK-M20
Article number (order number)	101157381
EAN (European Article Number)	4030661180113
eCl@ss number, version 12.0	27-27-26-02
eCl@ss number, version 11.0	27-27-26-02
eCl@ss number, version 9.0	27-27-26-02
ETIM number, version 7.0	EC002592
ETIM number, version 6.0	EC002592
Approvals - Standards	
Certificates	cULus
	CCC
General data	
Standards	EN IEC 60947-5-1
	EN ISO 13849-1
	EN ISO 14119
Coding level according to EN ISO 14119	Low
Working principle	mechanical

General data

Housing material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Gross weight	115 g

General data - Features

Number of actuating directions	3
Number of safety contacts	2
Number of cable glands	3

Safety classification

Standards	EN ISO 13849-1
Performance Level, up to	c
Category	1
B10D Normally-closed contact (NC)	2,000,000 Operations
Note	Electrical life on request.
Note	at 10% I _e and ohmic load
Mission time	20 Year(s)

Safety classification - Fault exclusion

Please note:	Can be used when fault exclusion for dangerous damage to the 1-channel mechanism is permissible and sufficient protection against manipulation is guaranteed.
Performance Level, up to	d
Category	3
Note	for 2-channel use and with suitable logic unit.
Mission time	20 Year(s)

Mechanical data

Mechanical lifetime, minimum	1,000,000 Operations
Latching force	30 N
Positive break travel	8 mm
Positive break force per NC contact, minimum	10 N
Positive break force, minimum	20 N
Actuating speed, maximum	2 m/s
Mounting	Screws
Type of the fixing screws	2x M6

Mechanical data - Connection technique

Type of electrical connection	Screw terminals M20 x 1.5
Cable entry	3 x M16 x 1,5
Termination	Screw terminals
Cable section, minimum	0.25 mm ²
Cable section, maximum	2.5 mm ²
Note	All indications including the conductor ferrules.
Allowed type of cable	solid single-wire
	solid multi-wire
	flexible

Mechanical data - Dimensions

Length of sensor	30 mm
Width of sensor	52 mm
Height of sensor	90 mm

Ambient conditions

IP Degree of protection	IP67
Ambient temperature	-30 ... +80 °C
Storage and transport temperature	-40 ... +85 °C
Permissible installation altitude above sea level, maximum	2,000 m

Ambient conditions - Insulation values

Rated insulation voltage Ui	500 V
Rated impulse withstand voltage Uimp	6 kV
Overvoltage category	III
Degree of pollution	3

Electrical data

Thermal test current	10 A
Required rated short-circuit current	1,000 A
Switching element	2 NC contact
Switching principle	slow action, positive break NC contact
Maximum switching frequency	4,000 /h
Material of the contacts, electrical	Silver

Electrical data - Safety contacts

Voltage, Utilisation category AC-15	230 VAC
Current, Utilisation category AC-15	4 A
Voltage, Utilisation category DC-13	24 VDC
Current, Utilisation category DC-13	4 A

Electrical data - Auxiliary contacts

Voltage, Utilisation category AC-15	230 VAC
Current, Utilisation category AC-15	4 A
Voltage, Utilisation category DC-13	24 VDC
Current, Utilisation category DC-13	4 A

Scope of delivery

Scope of delivery	Actuator must be ordered separately.
-------------------	--------------------------------------


Pictures

Product picture (catalogue individual photo)




ID: kaz16f01
[| 918.99 KB | .jpg | 1000 x 1621 Pixel](#)
[| 64.93 KB | .jpg | 216 x 350 Pixel](#)
[| 130.36 KB | .png | 210 x 340 Pixel](#)

Dimensional drawing basic component



ID: 1az16g01
[| 157.77 KB | .jpg | 999 x 1342 Pixel](#)
[| 10.01 KB | .png | 209 x 281 Pixel](#)

Switch travel diagram



ID: kaz16s02
[| 56.17 KB | .jpg | 1000 x 350 Pixel](#)
[| 2.06 KB | .png | 210 x 74 Pixel](#)

Diagram



ID: k2o--k01
| 48.77 KB | .jpg | 1000 x 355 Pixel
| 2.27 KB | .png | 210 x 75 Pixel

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on: 12/08/2026, 17:18