



Z4V7H 335-11Z-M20

- Metal enclosure
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- 40,5 mm x 76 mm x 38 mm
- Actuator heads can be repositioned by 4 x 90°
- only for positioning tasks
- Design to EN 50041

Data

Ordering code

Product type description	Z4V7H 335-11Z-M20
Article number (order number)	151161691
eCl@ss number, version 12.0	27-27-06-01
eCl@ss number, version 11.0	27-27-06-01
eCl@ss number, version 9.0	27-27-06-01
ETIM number, version 7.0	EC000030
ETIM number, version 6.0	EC000030

Approvals - Standards

Certificates	cULus
	CCC

General data

Housing construction form	Norm construction design
Housing material	Light alloy die-casting
Housing coating material	painted
Lever material	Metal film
Gross weight	315 g

Safety classification

Standards	BG-GS-ET-15
	EN ISO 13849-1
	EN IEC 60947-5-1
Mission time	20 Year(s)

Mechanical data

Actuating element	Roller lever
Roller material	Plastic
Mechanical lifetime, minimum	30,000,000 Operations
Actuating speed, maximum	2.5 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Actuating torque, minimum	0.3 Nm

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
Cable section, minimum	0.75 mm ²
Cable section, maximum	2.5 mm ²
Note	All indications including the conductor ferrules.

Mechanical data - Dimensions

Length of sensor	57.3 mm
Width of sensor	40.5 mm
Height of sensor	173.5 mm

Ambient conditions

IP Degree of protection	IP67
	IP65
Ambient temperature	-30 ... +80 °C

Electrical data

Thermal test current	10 A
Required rated short-circuit current	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A

Electrical data

Utilisation category DC-13	24 VDC
Utilisation category DC-13	4 A
Switching element	1 NO contact, 1 NC contacts
Switching principle	Snap action
Maximum switching frequency	5,000 /h
Material of the contacts, electrical	Silver


Pictures

Product picture (catalogue individual photo)




ID: k335hf02
| 914.51 KB | .jpg | 1000 x 2729 Pixel
| 23.06 KB | .jpg | 128 x 350 Pixel
| 123.55 KB | .png | 210 x 573 Pixel

Dimensional drawing basic component




ID: 1-335g01
| 105.79 KB | .jpg | 1000 x 697 Pixel
| 4.51 KB | .png | 210 x 146 Pixel

Dimensional drawing actuator



ID: 1h355g02
| 104.88 KB | .jpg | 1000 x 691 Pixel
| 9.58 KB | .png | 210 x 145 Pixel

Switch travel diagram



ID: kh335s02
| 98.37 KB | .jpg | 1000 x 548 Pixel
| 2.98 KB | .png | 210 x 115 Pixel

Diagram



The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 13/08/2026, 15:15