



Z4V7H 335-11Z-M20-RMS

- with brass roller
- Metal enclosure
- Wide range of alternative actuators
- Good resistance to oil and petroleum spirit
- 40,5 mm x 76 mm x 38 mm
- Actuator heads can be repositioned by 4 x 90°
- only for positioning tasks
- Design to EN 50041

Data

Ordering code

Product type description	Z4V7H 335-11Z-M20-RMS
Article number (order number)	151173807
eCl@ss number, version 12.0	27-27-06-01
eCl@ss number, version 11.0	27-27-06-01
eCl@ss number, version 9.0	27-27-06-01
ETIM number, version 7.0	EC000030
ETIM number, version 6.0	EC000030

Approvals - Standards

Certificates	cULus
	CCC

General data

Housing construction form	Norm construction design
Housing material	Light alloy die-casting
Housing coating material	painted
Lever material	Metal film
Gross weight	300 g

General data - Features

Number of auxiliary contacts	1
Number of safety contacts	1

Safety classification

Standards	BG-GS-ET-15
	EN ISO 13849-1
	EN IEC 60947-5-1
Mission time	20 Year(s)

Mechanical data

Actuating element	Roller lever
Roller material	Brass
Mechanical lifetime, minimum	30,000,000 Operations
Actuating speed, maximum	2.5 m/s
Note (Actuating speed)	Actuating speed with actuating angle 30° to switch axis
Note Bounce duration	Bounce duration in accordance with actuating speed
Actuating torque, minimum	0.3 Nm

Mechanical data - Connection technique

Termination	Screw terminals M20 x 1.5
Cable section, minimum	0.75 mm ²
Cable section, maximum	2.5 mm ²
Note	All indications including the conductor ferrules.

Mechanical data - Dimensions

Length of sensor	57.3 mm
Width of sensor	40.5 mm
Height of sensor	173.5 mm

Ambient conditions

IP Degree of protection	IP67
	IP65
Ambient temperature	-30 ... +80 °C

Ambient conditions - Insulation values

Rated insulation voltage U_i	500 V
Rated impulse withstand voltage U_{imp}	6 kV

Electrical data

Thermal test current	10 A
Required rated short-circuit current	1,000 A
Utilisation category AC-15	230 VAC
Utilisation category AC-15	4 A
Utilisation category DC-13	24 VDC
Utilisation category DC-13	4 A
Switching element	1 NO contact, 1 NC contacts
Switching principle	Snap action
Maximum switching frequency	5,000 /h
Switchover time, maximum	2 ms
Material of the contacts, electrical	Silver

Pictures


Product picture (catalogue individual photo)



ID: k335hf06

947.33 KB	.jpg	1000 x 2729 Pixel
24.99 KB	.jpg	128 x 350 Pixel
126.27 KB	.png	210 x 573 Pixel

Dimensional drawing basic component




ID: 1-335g01

| 105.79 KB | .jpg | 1000 x 697 Pixel

| 4.51 KB | .png | 210 x 146 Pixel

Dimensional drawing actuator




ID: 1h355g02

| 104.88 KB | .jpg | 1000 x 691 Pixel

| 9.58 KB | .png | 210 x 145 Pixel

Switch travel diagram




ID: kh335s17

| 85.86 KB | .jpg | 1000 x 548 Pixel

| 2.36 KB | .png | 210 x 115 Pixel

Switch travel diagram



ID: kh335s02

| 98.37 KB | .jpg | 1000 x 548 Pixel

| 2.98 KB | .png | 210 x 115 Pixel

Diagram



ID: k1o1sk01

| 52.24 KB | .jpg | 1000 x 407 Pixel

| 2.58 KB | .png | 210 x 85 Pixel

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 17/08/2026, 16:03